

## EA Series UPS Specifications

VA Rating	600VA	800VA	1200VA	1500VA
Real Power Rating	360W	480W	720W	900W
<b>Input</b>				
Phase	Single Phase +N			
Voltage	120V ± 25%			
Frequency	60Hz ± %10			
<b>Output</b>				
Voltage	120V ± 25%			
Waveform	Sine Wave (Mains); Square Wave (Battery)			
Frequency	60Hz ± 1% (Battery)			
Crest Factor	3:1			
Transfer	≤ 10 ms			
Socket	Socket Type Can Chosen			
<b>Battery</b>				
Type	Lead-Acid Maintenance-Free Battery			
Quantity	1*12V/7AH	1*12V/8AH	2*12V/7AH	2*12V/8AH
Recharge	90% Capacity after 8 Hours			
Backup	10~20 Minutes, Depending on Load and Model			
<b>General</b>				
Transformer	Toroidal Transformer (New Design)			
Surge	RJ11&RJ45 for Modem and LAN, Cable Attached (Optional)			
Communication	RS232 or USB (Optional)			
Noise	<45db(1 Meter)			
Temperature	0~40°C			
Humidity	20~90%(Non-condensing)			
Dimension(mm)	320*163*96		390*223*127	
Packing Dimension	375*145*230		450*180*295	

