



## SPECIAL FEATURES

- Universal AC input / full range
- High efficiency
- DC adjust range
- LED Power indicated
- Output reverses protection
- Free air cooling convection
- 129\* 98\* 38 mm
- Weight 0.33 kgs/pcs
- 1 year warranty

## SPECIFICATION

### Output

- Maximum power.....35 Watts
- DC adjust range.....  $\pm 10\%$  of rating output voltage
- Hold-up time.....> 30 ms at 230Vac/ 50Hz
- Rise time.....< 40ms
- Over Voltage Protection...115% ~ 135% of rated output
- Over Power Protection.....105% ~ 150%, auto-recovery
- Short Circuit Protection.....Hiccup mode
- Connector.....5P / 9.5mm pitch terminal block

### Input

- Input range.....90-264Vac
- Frequency.....47-63Hz
- AC inrush current...Cold start, 30A @ 115Vac; 50A @ 230Vac
- EMI/RFI.....FCC Part 15J, Class A & CISPR 22 Class A

### Operating temperature

- 0 °C to +45 °C @100%; -10 °C @ 80%; 60 °C @ 60% load
- Storage temperature: -20 °C to +80 °C
- Free air cooling convection

Model	IM350C05-1M	IM350C12-1M	IM350C24-1M
Output	V1	V1	V1
Voltage	+5V	+12V	+24V
Max. Load	7A	3A	1.5A
Efficiency	>70% @ 115 Vac/60 Hz	>75% @ 115 Vac/60 Hz	>75% @ 115 Vac/60 Hz